






# HYDROMARINE HEAT PUMP 6, 7.5 & 10 TONS

TITANIUM HEAT EXCHANGER FOR USE IN ALL AQUATIC CHILLING/HEATING APPLICATIONS




MODEL NUMBER	Tonnage / BTUH	SPECIFICATIONS			DIMENSIONS			POWER OPTIONS	
		Vertical Air Discharge (CFM)	Δ PSI at max flow	Water Flow Range (GPM)	Length (L)	Width (W)	Max. Height (H)	208-230V / 3 ph. MCA	460V / 3 ph. MCA
DH-HP-6	6 / 72 000	6 000	<4	30 - 120	84"	48"	61"	28	12
DH-HP-7.5	7.5 / 90 000	6 000	<4	50 - 150	84"	48"	61"	35	18
DH-HP-10	10 / 120 000	6 000	<4	50 - 150	84"	48"	61"	42	23

\*MCA is the highest steady-state electrical current that the unit should see when operating correctly



**FLOW SWITCH NOTE:**  
FLOW SWITCH MUST BE INSTALLED HORIZONTALLY ON INLET OF HEAT EXCHANGER, WITH MINIMUM STRAIGHT PIPE DISTANCES BEFORE AND AFTER AS SHOWN IN DRAWING. OPTIONAL FACTORY MOUNT & WIRE.



**THERMOWELL NOTE:**  
MUST BE INSTALLED ON INLET PIPING TO HEAT EXCHANGER.

### NOTES:

- CONDENSER AND SKID MOUNTED ON 4" MARINE GRADE ALUMINUM SQUARE TUBE
- Gr.2 TITANIUM TUBE HEAT EXCHANGER COILS
- NORMAL OPERATING AMBIENT AIR TEMPERATURE: 50 F - 115 F
- ALL CONDENSING UNITS HAVE EER OF 11 OR BETTER.
- TOP DISCHARGE AREA SHOULD BE UNRESTRICTED FOR 48 INCHES MINIMUM
- AVOID PLACING UNIT IN DIRECT AREA OF ROOF RUNOFF OR CONSTANT WATER FLOW
- CONSULT **CARRIER** SPECIFIED CONDENSER CLEARANCES WHEN PLACING UNIT(S)
- SCH 80 PVC SHELL CONSTRUCTION WITH REMOVABLE FLANGED ENDS
- ALL 316 SS BASE, JACKET AND HARDWARE
- TEMPERATURE CONTROLLER CAN BE SET +/- 0.1° F/C
- UNIT ARRIVES CHARGED WITH R-410A REFRIGERANT

### OPTIONS:

- LOW AMBIENT MOTORMASTER KIT FOR OUTDOOR TEMPERATURES -0°F TO 55°F
- MARINE CONDENSER COATING FOR COASTAL APPLICATIONS
- NON-FUSED DISCONNECT
- 115V CONVENIENCE OUTLET
- HAIL GUARD



## Delta Hydronics

9100 Bolton Ave., Hudson, FL, 34667 (727) 861-2421 - info@deltahydro.com